### CIRRUS DOCKET NO. 1111-CA

# PATENT SERIAL NO. 09/695,706

### VERSION WITH MARKINGS TO SHOW CHANGES MADE

#### IN THE CLAIMS

- (1) Cancel claim 1 has been cancelled.
- (2) Claim 2 has been rewritten as follows:
- 1 2. (Amended) [The circuit of claim 1 further comprising an analog to digital converter
- 2 connected between said amplifier and said output] A circuit comprising:
- 3 <u>a.</u> <u>an input,</u>
- 4 b. an output,
- 5 c. a chopper stabilized, multistage feedforward amplifier connected between said input
- 6 and said output, and
- 7 <u>d.</u> an analog to digital converter connected between said amplifier and said output.
- 1 (3) Claim 11 has been rewritten as follows:
- 2 11. (Amended) The circuit of claim [1] 2, further comprising a plurality of integrators connected
- 3 between said amplifier and said output.
  - (4) Claim 12 has been rewritten as follows:
- 1 12. (Amended) The circuit of claim [1] 2 fabricated on an integrated circuit.
  - (5) Claim 28 has been cancelled.

## CIRRUS DOCKET NO. 1111-CA

PATENT SERIAL NO. 09/695,706

- (6) Claim 29 has been rewritten as follows:
- 1 29. (Amended) [The] A method of [claim 28 further] designing an integrated circuit comprising
- 2 the [step] steps of:
- 3 specifying an input, an output and a chopper stabilized, multistage, feedforward amplifier
- 4 connected between said input and said output; and
- 5 specifying a delta sigma modulator to be connected between said amplifier and said output.
  - (7) Claim 30 has been cancelled.
  - (8) Claim 31 has been rewritten as follows:
- 1 31. (Amended) [The] A method of [claim 30 further] fabricating an integrated circuit comprising
- 2 the [step] steps of:
- providing an input, an output and a chopper stabilized, multistage, feedforward amplifier
- 4 connected between said input and said output; and
- 5 providing a delta sigma modulator to be connected between said amplifier and said output.

AUSTIN\_1\176241\1 10/24/2001 - 2836-P147US